

**1. Name and description of the product**

COMMERCIAL NAME	DESCRIPTION
<b>BIKMOR 2002-M7.5F</b>	Grey mortar for manual rendering works of brick or concrete block walls.
<b>BIKMOR 2002-M7.5FH (W2)</b>	Waterproof grey mortar for manual rendering works of brick or concrete block walls.
<b>BIKREV 3000P</b>	Grey mortar for rendering works of brick or concrete block walls. Especially indicated for spraying.
<b>BIKREV 3300PB</b>	White mortar for rendering works of brick or concrete block walls. Especially indicated for spraying.
<b>BIKREV 3300PH (W2)</b>	Waterproof grey mortar for rendering works of brick or concrete block walls. Especially indicated for spraying.
<b>BIKREV 3300 PBH (W2)</b>	Waterproof white mortar for rendering works of brick or concrete block walls. Especially indicated for spraying.
<b>BIKREV 3000P-CSIV</b>	Grey mortar for rendering works of brick or concrete block walls. Especially indicated for spraying. Strength category CSIV.
<b>BIKREV 3300PB-CSIV</b>	White mortar for rendering works of brick or concrete block walls. Especially indicated for spraying. Strength category CSIV.
<b>BIKREV 3300PH-CSIV (W2)</b>	Waterproof grey mortar for rendering works of brick or concrete block walls. Especially indicated for spraying. Strength category CSIV.
<b>BIKREV 3300 PBH-CSIV (W2)</b>	Waterproof white mortar for rendering works of brick or concrete block walls. Especially indicated for spraying. Strength category CSIV.
<b>BIKREV 3200</b>	Waterproof grey mortar for fine finishing of brick or concrete walls that have been previously rendered using cement based mortar. For interiors as well as exteriors.

**2. Manufacturer's name and address**

**MORTEROS Y REVOCOS BIKAIN, S.A.**  
Barrio Aldebarrena, nº 18, Mañaria, 48212  
(Bizkaia) [www.bikain.com](http://www.bikain.com)

**3. System for evaluating and verifying the constancy of performance**

SYSTEM 4

**4. Dangerous substances**Consult the applicable product Safety Data Sheets that are available on Website [www.bikain.com](http://www.bikain.com).

## 5. Intended uses and declared performances

Industrial mortars for rendering/finish plaster for normal masonry work (GP) on walls, ceilings, pillars and interior walls (EN 998-1).

CHARACTERISTICS	Compressive strength	Adhesive strength	Bulk density of hardened mortar	Reaction against fire	Water absorption	Water vapour permeability	Thermal conductivity tabulated P50%	Durability
STANDARDS	EN 1015-11	EN 1015-12	EN 1015-10	Section 5.3.3 EN 998-1	EN-1015-18	EN 1015-19	Table A.12 EN 1745	
Unit	Class	N/mm <sup>2</sup>	g/cm <sup>3</sup>	Class	kg/m <sup>2</sup> .min <sup>0.5</sup>		W/Mk	-
BIKMOR 2002-M7.5F	CSIV	~ 0.1 (A-B)	1.5-1.7	A1	W0	PND	0.61	PND
BIKMOR 2002-M7.5FH (W2)	CSIV		1.5-1.7		W1 m0.4 W2 m0.2	m15	0.61	
BIKREV 3000P	CSIII		1.3-1.5		W0	PND	0.45	
BIKREV 3300PB	CSIII		1.3-1.5		W0	PND	0.45	
BIKREV 3300PH (W2)	CSIII		1.3-1.5		W1 m0.4 W2 m0.2	m15	0.45	
BIKREV 3300 PBH (W2)	CSIII		1.3-1.5		W1 m0.4 W2 m0.2	m15	0.45	
BIKREV 3000P-CSIV	CSIV		1.5-1.7		W0	PND	0.61	
BIKREV 3300PB-CSIV	CSIV		1.3-1.5		W0	PND	0.45	
BIKREV 3300PH-CSIV (W2)	CSIV		1.5-1.7		W1 m0.4 W2 m0.2	m15	0.61	
BIKREV 3300 PBH-CSIV (W2)	CSIV		1.3-1.5		W1 m0.4 W2 m0.2	m15	0.45	
BIKREV 3200	CSIV		1.5-1.7		W2 m0.2	m15	0.61	

- The performance of the products identified in paragraph 1 are compliant with the performances declared in paragraph 5.
- This declaration of performance is issued under the sole responsibility of the manufacturer listed in paragraph 2.

Signed by and for the manufacturer:

Igone Azkarate,  
Head of Laboratory  
Mañaria, on the 1st of September of 2018 (vs4)

