

1. Name and description of the product

COMMERCIAL NAME	DESCRIPTION
BIKATHERM 4200	Waterproof grey mortar for bonding and cladding expanded polystyrene boards (EPS).

2. Manufacturer's name and address

MORTEROS Y REVOCOS BIKAIN, S.A.
Barrio Aldebarrena, nº 18, Mañaria, 48212
(Bizkaia) www.bikain.com

3. System for evaluating and verifying the constancy of performance

SYSTEM 4

4. Dangerous substancesConsult the applicable product Safety Data Sheets that are available on Website www.bikain.com.**5. Intended uses and declared performances**

Industrial mortars for plastering/finish plaster (GP) on walls, ceilings, pillars and interior walls (EN 998-1).

CHARACTERISTICS	STANDARDS	Unit	Values
Compressive strength	EN 1015-11	Class	CSIV
Adhesive strength	EN 1015-12	N/mm ²	~ 0.8 (A-B)
Bulk density of hardened mortar	EN-1015-10	g/cm ³	1.3-1.5
Reaction against fire	Apdo. 5.3.3 EN 998-1	Class	F
Water absorption	EN-1015-18	kg/m ² .min ^{0.5}	W2 m0.2
Water vapour permeability	EN 1015-19		m15
Thermal conductivity <i>tabulated P50%</i>	Table A.12 EN 1745	W/Mk	0.45
Durability		-	PND

- The performance of the products identified in paragraph 1 are compliant with the performances declared in paragraph 5.
- This declaration of performance is issued under the sole responsibility of the manufacturer listed in paragraph 2.

Signed by and for the manufacturer:

Igone Azkarate,
Head of Laboratory
Mañaria, on the 1st of September of 2018 (vs2)

BIKAIN, S.A.
Aldebarrena, 18 – 48212 Mañaria (Bizkaia)
+34 946 202 496
www.bikain.com
info@bikain.com

